



TECHNICAL DATA SHEET LTP MATTSTONE MATT FINISH IMPREGNATING SEALER

A completely natural, matt finish for terracotta, quarry tiles, slate, stone, marble and brick and external paving. Enhances the colour and texture of floors. Helps protect against staining. Strongly repels water. Allows surface to breath.

Important: Mattstone may need to be used in conjunction with a surface sealer on more absorbent, rough surface floors.

Directions for use:

Shake the bottle prior to use. Ensure surface to be treated is completely clean, dry and free from cement and grout stain (see LTP Grout Stain Remover). Apply 2-3 coats of LTP Mattstone with a paint brush allowing at least four hours between coats. More absorbent floors may require further coats and on such floors the product should be generously applied. 1-2 hours after the last application, rub over the floor with a soft fluff free cloth to obtain a uniform finish and remove any material not yet absorbed. LTP Mattstone will dry after about two hours, but will take a further three days to become fully resistant. N.B. Mattstone will help to inhibit oil-based stains but such spillages should be wiped up immediately.

Coverage:

Lower porosity floors	-approximately 1-2 litres per 10m ² of floor
Higher porosity floors	-approximately 3-4 litres per 10m ² of floor

Attention: FLAMMABLE

Keep out of reach of children

Use in well ventilated areas

Use gloves to apply

Avoid contact with eyes and skin

In case of contact with eyes rinse immediately with plenty of water and seek medical advice

In case of swallowing seek medical advice

After contact with skin, wash with soap and water

Toxic to aquatic organisms.

Maintenance: Routinely sweep the floor and wash with LTP Waxwash. Ensure that areas where the seal has been worn or damaged are resealed with Mattstone. Apply a fresh coat of Mattstone to your floor should it begin to show signs of stain absorption. This should be done after the floor has been washed and allowed to dry thoroughly.

For any technical questions, please ring technical helpline: 01823 666 213.

Click to see all [stone maintenance products](#)